

Vertica 50

6 x 3",
Passive Column Speaker

ENNE



Key Feature

- Compact & versatile
- Powered from the sub unit
- DSP presets for wide applications
- Weather proof components
- Easy to use, easy to install
- Portable
- Available in black or white

Specifications

Frequency Range (-10 dB)¹: 150 Hz - 20 KHz

Frequency Response (± 3 dB)¹: 180 Hz - 20 KHz

Sensitivity (1w@1m): 97 dB

Nominal Impedance: 32 Ohms

Peak Maximum SPL: 125 dB

Power Rating: 150W / 300W / 600W

(Continuous²/Program/Peak)

Coverage Pattern: 15° \pm 5° x 100° (V x H)

Dimension (H x W x D): 532 x 89 x 116 mm

Net Weight: 7 Kg

HF Driver: 6 x 3" speaker with 0.75" voice coil

Input Connectors: 2 x Neutrik® Speakon® NL4MP

Enclosure Construction: 1.5 mm stainless steel

Micro-textured epoxy paint

Applications

- PA system
- Clubs & Theatres
- Multi-function hall
- Solo artists, band, DJ
- Education
- Transportation

Description

The Vertica 50 is a passive column speaker part of the Vertica series. The Vertica cabinets are compact, modular and powerful and the complete serie include two sub units and two column models.

The Vertica 50 uses 6 x 3" (0.75" voice coil) neodymium transducers offering a coverage of 15° +/-5° V x 100° H and 119dB SPL.

Weight has been left as low as possible providing easy set up in fixed installation as well as easy transport for portable applications.

The Vertica 50 is powered from the sub bass units which include a Digital Signal Processor offering different presets to cover a wide range of sound applications.

1. In full-space.

2. IEC Filtered Pink Noise with 6dB Crest Factor, 2 hours duration.