

Aries 2

2-way, 12"
Bass-Reflex Speaker

ENNE



Applications

- Theater, multi-function hall
- Conference meeting room
- Live performance venues
- KTV, club, bar or voice applications
- Satellite speaker for use together with subwoofers
- Portable sound reinforcement

Description

Aries is a multi-function series which consists 10", 12", 15" 2-way full-range loudspeakers and 18" subwoofer. Aries is designed for different uses, such as theatre, conference hall, nightclub or live performance. It can offer unprecedented performance and utility with its unique design features, functional cabinet ideas and meticulous tuned sound characteristics.

Aries use excellent compression driver which can delivers super smooth frequency response and clear bright sound. Distinctive horn technology provides precise directivity to the range of loudspeaker coverage. Well-designed crossover network provides smooth transition from HF to LF and perfect combination, also perfectly protects HF unit.

KEY Features

- Excellent performance for multi-purpose application
- High-power capacity, Compact cabinet
- 1.4" Composite material diaphragm HF compression driver
- 12" Ferrite magnet LF component
- 90° x 60° coverage pattern, rotatable horn for vertical or horizontal application
- Crossover mode available, Bi-amp or Passive, flexible for different applications
- High precision crossover for optimal frequency response and performance
- High frequency driver protection
- Fashion looking with dustproof protective steel grille
- Pole mount at the bottom for satellite applications
- 16 x M10 Suspension points for flexibility of installation

Specifications

System Type:	12" , 2-way, bass-reflex speaker
Frequency Range (-10 dB) ¹ :	45Hz - 20kHz
Frequency Response (±3dB) ¹ :	50Hz - 18kHz
Sensitivity (1w@1m):	LF: 98dB / HF: 109dB Passive: 99dB
Nominal Impedance:	8Ohms
Peak Maximum SPL:	LF: 131dB / HF: 135dB Passive: 132dB
Power Rating: (Continuous ² /Program/Peak)	LF: 600W / 1200W / 2400W HF: 90W / 180W / 360W Passive: 600W / 1200W / 2400W
Coverage Pattern ³ :	90° x 60°(Rotatable)
Dimension (H x W x D):	661mm x 390mm x 374mm
Net Weight:	25Kg
LF Driver:	1 x 12", Φ3" voice coil
HF Driver:	1 x 1.4", Φ2.5" voice coil
Input Connectors:	2 x Neutrik® Speakon® NL4MP
Suspension/Mounting:	M10 x 16

1. Calculated based on power rating and sensitivity


2. IEC Filtered Pink Noise with 6dB Crest Factor, 2 hours duration

3. 500Hz to 4kHz.


Aries 2

2-way, 12", Bass-Reflex Speaker


Frequency Response



Impedance Response



Dimension



ENNE Inc. (USA)
650 N San Mateo Drive. San Mateo, California, USA
CA 94401

ENNE Inc. (HK)
香港九龍彌敦道345號宏利公積金大廈10樓1001-1003室
Tel (852) 2301 1130
Fax (852) 2301 1299

ENNE Inc. (CN)
廣州市番禺區鐘村鎮鐘一村高沙工業區自編3號
Tel (020) 8386 3535 8386 3598
Fax (020) 8386 3550

ENNE